

wePresent[®] 9

High-end Multimedia Wireless Presentation System

WiFi 802.11b/g/n standards



1-to-4 Presentation

Project your Windows screen or stream video content to 4 screens simultaneously



Remote Desktop

Control the projecting PC remotely by simply plugging standard USB keyboard or mouse into WP-920 device



WiFi AP-Client mode

Allow WP-920 to join the existing WiFi Access Point wirelessly for flexible network deployment in enterprise environment



SNMP Manager

Manage and configure multiple WP-920 device(s) settings through friendly SNMP application



Faster Screen Projection for Mac PCs

Increase the Mac projection speed up to 5 times!



DirectX application projection

Support DirectX application projection, such as AutoCAD, ProE and 3D PC games.





4-to-1 Split Screen Projection




1-to-4 Screen Projection

Basic features

- Plug-and-Show (PnS) Driverless Installation
- 4-to-1 Split Screen Projection
- Near Real-time Screen and Audio Projection
- Conference Control
- 1080p Video/Audio Streaming
- Changeable Customized Image of Splash Screen
- Multiple Users Access
- Web management including software download and device settings
- Session Login Code, WEP/WPA key, and GateKeeper setting for security purpose
- Macintosh® Wireless Projection
- Windows Mobile Smartphone Wireless Projection (MobiShow)
- Wireless Access Point usage
- Equipped with RJ-45 port for wired LAN links which allows users to browse Internet



wePresent Software User Interface



MobiShow Software User Interface

Specification

Standards	IEEE 802.11b/g/n 2.4GHz IEEE 802.3 (10BASE-T) / IEEE 802.3u (100BASE)
Security	IEEE Standard 64/128 bit WEP / WPA / WPA2
Management	Web-based configuration
Supported Output Resolution	SVGA (800x600) / XGA (1024x768) / WXGA(1280x768) / WXGA+(1280x800)
Supported Operation	Windows XP / Vista / 7, Windows Mobile 5 and above, Mac OS X 10.5 and above
SystemSupported media format	MP3, MPEG1 (mpg, dat), MPEG2 (mpg, vob), MPEG4 (wmv9, asf), DivX3/4/5, XVID, H.264
Power	External power adaptor DC 5V 2.5A
Interfaces	15-pin VGA RJ-45 USB 2.0 Reset Button Stereo Phone Jack
Dimension and weight	Dimension: 117 x 140 x 27mm Weight: 279g
Certificate	FCC/CE